




TENTATIVE CLASSIFICATION OF "CLEAN" GRAVELLY GEOMATERIALS

SOIL	GC* %	SC* %	FC* %
CLEAN SAND	< 10	≥ 85	< 5
GRAVELLY SAND	< 50	≥ 50	< 5
SANDY GRAVEL	≥ 50	< 50	< 5
CLEAN GRAVEL	≥ 85	< 10	< 5

For low plasticity, fines matrix FC < 15%

- Drained response under monotonic and very low frequency cyclic loading
- Excess pore pressure generated under higher frequency cyclic loading
- (*) content of gravel (GC), sand (SC) and fines (FC) respectively

GRAVELLY DEPOSIT OVERLAYING SOFT ROCK




GRAVELLY GEOMATERIALS ENGINEERING RELEVANCE

- Important transportation infrastructures, growing demand for optimized design of direct foundations.
 - e.g.: Akashi Kaikyo (q = 1.0 MPa), Messina Straits (q = 1.5 Mpa) suspension bridges.
- Construction materials for embankment dams, highways, high speed railways.
 Must be checked against vibratory loadings originated by earthquakes wind, and traffic.
- Susceptibility of natural deposits to liquefaction and cyclic mobility.
 Many examples of gravelly deposits liquefaction, e.g.: Andrus (1994), Ishihara (1996),
 Andrus and Stokoe (2000)



THRESHOLD BOUNDARY SURFACES IN PRINCIPAL STRAIN SPACE (QUALITATIVE) Jamiolkowski and Lai (2000)




VISCOUS NATURE OF THRESHOLD STRAINS

Influence of strain rate on $arepsilon_t^{\,\ell}$

Influence of creep on yield locus Y2

Tatsuoka and Shibuya (1991)

Tatsuoka et al. (1997)




G-130

BAN-08

INFLUENCE OF MEAN EFFECTIVE STRESS ON THRESHOLD STRAINS OF NO SANDS*


Adapted from Derendeli (2001)



CONSTITUTIVE MODELS USED TO DESCRIBE SOIL MECHANICAL BEHAVIOUR

Jamiolkowski and Lai (2000) 🛚

Non-linear Elasto-Visco-Plastic



Non-linear Elasto-Plastic

Non-linear Visco-Elastic




Figure 1

Phenomenological Soil Response



Non-linear Hypo-Elastic

Linear Visco-Elastic



Stress-Strain Path Stress-Strain Magnitude Stress-Strain Rate Stress-Strain Duration

- Static-Monotonic Loading
- Dynamic Loading

Linear Hypo-Elastic

AFTER DEPOSITIONAL REDUCTION OF POROSITY

Palmer and Barton (1987), Barton et al. (1993), Cresswell (1999)


MECHANICAL*: reorientation and repacking

- CHEMICAL*: intergranular pressure dissolution, contact area and roughness increase
- CEMENTATION: precipitation of minerals in pore space

(*) Occurrence of locked sands and gravels, characterized by D_R > 100% Desseault and Morgenstern (1979), Palmer and Barton (1987).

TENTATIVE PLOT OF RELATIVE DENSITY VS. GEOLOGICAL AGE

Palmer and Barton (1987).




TWO-DIMENSIONAL MODEL OF LOCKED SAND


Cresswell (1999)


Grain can be easily removed by gentle brushing

Grain held in by interlocking < asperities



GRAVELLY DEPOSITS ON SIGILIAN SHORE






Silica sand and gravel of Holocene (≅10000y) and Pleistocene (>500000y) age:

- Similar grading and mineralogical composition
- Deposited in similar environment; deltaic and shallow sea
- Comparable penetration resistance
- Quite different shear wave velocity


MESSINA STRAIT CROSSING TYPES OF CEMENTATION IN MESSINA GRAVELS FORMATION

(Adapted after Bosi, 1990)


CaCO₃ coatings.




Coatings of Fe and Mn oxides.




Voids filled with CaCO₃.




Silty clay matrix lightly cemented with CaCO₃.



Sand matrix cemented with CaCO₃.



Silty clay matrix lightly cemented with Fe and Mn oxides.




Type 4, intermediate between 3rd and 5th;


Type 6, intermediate between 5th and 7th.

MULTIPLE-SIZED COARSE GRAINED GEOMATERIAL


Lin (1986), Kuerbis et al. (1988), Thevanayagam (1998,1999a, 1999b), Thevanayagam and Liang (2001)




a) Gravel, SC<10%



SC<SC,



b) Sandy gravel, c) Sand and gravel, SC, <SC<SC/



d) Gravelly sand, SC>SC/

SC=Sand fraction; GC=Gravel fraction; SC_f=Threshold sand fraction; SC_ℓ =Limit sand fraction

- For mixes a and the global void ratio e reflects the internal interparticle contacts
- For mixes b and c it is necessary to refer to the equivalent sand fraction es and gravel fraction e_o void ratio respectively, which control the number of interparticle contacts.

Mechanical response of coarse grained geomaterials primarily affected by contacts density per grain



PENETRATION TESTING


- Selection of penetration methods controlled first by size of gravelly particles, then by in situ soil density
- Every-day practice mainly limited to SPT and LPT
- N_{SPT} and N_{LPT} blow-count normalization with respect to energy transmitted to driving rods and to effective overburden stress:

$$(N_1)_{60} = C_N \cdot \frac{ER}{60} \cdot N$$
; $N = N_{SPT}$ or N_{LPT}

- How particle size affects N_{SPT} vs N_{LPT} results still to be clarified*, Daniel (1999), Daniel et al. (2004)
- In special circumstances, CPT, S-CPT, DMT, S-DMT, can be attempted
- (*) Relevant when employing engineering correlation for soil properties.

LARGE PENETRATION TEST USED IN ITALY

Crova et al. (1992)



G-130 BAN-17

N_{SPT} VERSUS N_{LPT} IN GRANULAR DEPOSITS

Location	Deposits	ER _{SPT} (%)	ER _{LPT} (%)	$\frac{N_{SPT}}{N_{LPT}}$	[N ₁₍₆₀₎] _{SPT} [N ₁₍₆₀₎] _{LPT}	D ₅₀ (mm)
San Prospero*	Po River sand	56	84	1.35 ± 0.43	0.91 ± 0.27	0.2 to 0.6
Messina strait	Holocene sand and gravel	65	85	1.12 ± 0.58	0.85 ± 0.47	0.5 to 21.3
	Pleistocene sand and gravel	60	85	1.45 ± 0.32	1.02 ± 0.25	0.2 to 44

(*) Site at which LPT has been calibrated against SPT.

RELATIVE DENSITY OF GRAVELLY SOILS FROM SPT AND LPT

Cubrinowski and Ishihara (1999)

$$\frac{(N_1)_{78}}{D_R^2} = C_D = \frac{9}{(e_{max} - e_{min})^{1.7}}$$


- Checked against laboratory tests on undisturbed samples
- Lack of specific ER measurements
- Postulated that the Japanese $N_{LPT} = N_{SPT}$ with ER = 78%
- e_{max} and e_{min} assessed by Kokusho and Tadashi (1997) method for gravelly soils

Further validation of Cubrinowski and Ishihara (1999) approach involving ER measurements strongly recommended.

RELATIVE DENSITY OF COARSE GRAINED SOILS FROM SPT AND LPT


Relationship between N₁/D²_R and void ratio range

Cubrinowski and Ishihara (1999)




Maximum and minimum void ratio of coarse grained soils

Adapted after Cubrinowski and Ishihara (1999)



G-130

BAN-09



G-130

BAN-10

GEOPHYSICAL METHODS

- Crucial in hard-to-sample geomaterials like gravelly soils
- Continuously growing relevance, applied to broad spectrum of problems
 - e. g.: Small strain stiffness (G_o , M_o) and damping ratio (D_o), Porosity (n), Saturation line*, Liquefaction susceptibility $f(V_s)$, Quality control (V_s) of laboratory samples and of soil improvement, ...

Of main Interest:

Borehole methods: CHT, DHT, ** ...

Penetration methods: S-CPT**, S-DMT**, ...

Surface methods: SASW

- (*) Applicable in loose deposits, $V_p < 1600 \text{ m/s}$
- (**) Two receivers mandatory

SOIL STIFFNESS FROM SEISMIC TESTS

- Shear modulus:
- Constrained modulus:
- Young's modulus:

 $G_o = \rho \cdot V_s^2$

 $M_o = \rho \cdot V_p^2$

 $E_o = \rho \cdot V_{p'}^2$

 V_s = shear wave

V_p = constrained compression wave

V_{p'} = unconstrained compression wave

BASIC ASSUMPTIONS:

Medium is infinite

Material is linear and elastic

Wave radius of curvature is infinite

VELOCITIES

ADVANCED SEISMIC METHODS ACTIVE SURFACE TECHNIQUE

Rix et al. (2001), Lai et al. (2002), Lai (2004)

MULTI-STATION METHOD AS OPPOSED TO CURRENT TWO-STATION METHOD

UNCOUPLED
OR
COUPLED
INVERSION

∫ OF PHASE VELOCITY → SHEAR WAVE VELOCITY PROFILE

OF ATTENUATION CURVE → MATERIAL DAMPING RATIO PROFILE

- DEPTH LIMITED BY RESTRICTION IN POWER OF IMPULSIVE AND HARMONIC SOURCES USED
- BETTER MEDIUM RESPONSE FUNCTIONS; DISPLACEMENT TRANSFER FUNCTIONS, i. e.: DISPLACEMENT PHASE AND DISPLACEMENT AMPLITUDES.

POROSITY OF GEOMATERIALS FROM MEASURED SEISMIC WAVE VELOCITIES


Lancellotta (2001), Foti et al. (2002)

$$n = \frac{\left[\rho_s^2 - \frac{4(\rho_s - \rho_f)K_f}{V_p^2 - 2\left(\frac{1 - v_s}{1 - 2v_s}\right)V_s^2}\right]^{0.5}}{2(\rho_s - \rho_f)}$$
Connected porosity


- soil particles Poisson ratio of soil skeleton mass **S** density
 - pore fluid bulk modulus of pore fluid
- Valid in fluid saturated media
- Medium excited in low frequency range, no relative motion between fluid and solid phases (Biot, 1956), $f_c < (40 \text{ to } 50) 10^3 \text{ Hz}$
- Influence of $0.10 \le v_s \le 0.20$ on computed n very small




Foti et al (2001)



POROSITY PREDICTED AFTER FOTI ET AL. (2001) AT FIRENZE SITE USING BIOT'S (1956) THEORY





SMALL STRAIN POISSON RATIO FROM SEISMIC TESTS

MONOPHASE MEDIUM:

$$v'_{o} = \frac{(V_{p}/V_{s})^{2} - 2}{2(V_{p}/V_{s}) - 2}$$

Yields soil skeleton v'_o in dry and far from saturation soils

TWO-PHASE SATURATED MEDIUM IN LOW FREQUENCY RANGE*,


Biot (1956), Foti et al. (2002): $V_p = f(K_s, K_f, G, n)$

 K_f = pore fluid $\int_{C}^{C} bulk$ G = Shear modulus of soil skeleton

 $\frac{K_s}{s}$ = soil particles \int modulus ρ = porous media mass density

- To evaluate v'_o three independent measurements (V_p , V_s , n) required
- In coarse grained geomaterials 0.12< $v'_{o} \le 0.20$, affected by $\sigma'_{vc}/\sigma'_{hc}$
- (*) No relative movement occurs between fluid and solid phases.

CURVES RECOMMENDED FOR CALCULATION OF CRR FROM SHEAR WAVE VELOCITY MEASUREMENTS - BASED ON CASE HISTORY DATA



Andrus et al. (1999), Andrus and Stokoe (2000).

<u>Data base:</u> Uncemented Holocene coarse grained soils, $5.9 \le M_W \le 8.3$, MSF and r_d after Idriss (1999)


Curves for FC ≤ 20% applicable to gravelly soils. In first approximation:

 $V_{s1}^t = 215 \text{ m/s when FC} \leq 5\%;$ $V_s^t = 215 - 0.5 \text{ (FC-5) m/s when FC} > 5\%$

 V_{s1}^{t} = limiting upper value of V_{s1} for liquefaction occurrence



LABORATORY EQUIPMENT



LARGE DIMENSIONS APPARATUSES

 $(D/D_{max} > 6)$

Wu Chi Kao (1986) RC

Yasuda and Matsumoto (1993, 1994) TS

Hoque (1996) TX

Anh Dan (2001) 77

Meng and Stokoe (2003) RC - FF

IMPORTANT REQUIREMENTS:

- Local axial and radial strain measurement
- Low compliance, frictionless loading frame
- Actuator able to apply constant rate of strain as well as small and large cyclic loading

Technical University of Torino triaxial cell, H = 600 mm, D = 300 mm



G-133 CAI-10



G-133

CAI-06







G-133 CAI-11



G-133 CAI-12



G-133

CAI-08

SMALL STRAIN YOUNG'S MODULUS EMPIRICAL RELATIONSHIP* ($\varepsilon \le \varepsilon_t^{\ell}$)

$$E_o(V) = C_E(V) F(e) (\sigma'_V)^{nv} p_a^{(1-nv)}$$

$$E_o(H) = C_E(H) F(e) (\sigma'_h)^{nh} p_a^{(1-nh)}$$

 C_E = dimensionless anisotropic material constant; p_a = 1 bar = reference stress

$$F(e) = \frac{1}{e^{x}}$$
 = Void ratio function, $1.3 \le x \le 1.5$

 σ'_{v} \ \ \ \ \ \ effective stress respectively

 $\left\{ \begin{array}{c} nv \\ nh \end{array} \right\}$

experimental stress exponents function of U_c

(*) Applies to uncemented geomaterials

SMALL STRAIN SHEAR MODULUS EMPIRICAL RELATIONSHIP* $(\gamma \leq \gamma_t^{\ell})$

$$G_o(VH) = C_G(VH)F(e)(\sigma'_V)^{nv}(\sigma'_h)^{nh}p_a^{(1-nv-nh)}$$

$$G_o(HH) = C_G(HH) F(e) (\sigma'_h)^{2nh} p_a^{(1-2nh)}$$

 C_G = dimensionless anisotropic material constant; p_a = 1 bar = reference stress

$$F(e) = \frac{1}{e^{x}}$$
 = Void ratio function, $1.3 \le x \le 1.5$

 $_{nh}^{nv}$

experimental stress exponents function of U_c

(*) Applies to uncemented geomaterials

SMALL STRAIN SHEAR MODULUS OF GRAVELLY SOIL UNDISTURBED vs. RECONSTITUTED* SPECIMENS

Hatanaka et al. (1988), Goto et al. (1987, 1992, 1994), Kokusho and Tanaka (1994), Yasuda et al. (1994), Hatanaka and Uchida (1995)

	D ₅₀ (mm)	U _c (-)	G ₀ (U) ** G ₀ (R)
HOLOCENE DEPOSITS	5.3 to 73.0	54 to 121	1.2 to 1.3
PLEISTOCENE DEPOSITS	1.8 to 53.0	9 to 60	2.0 to 3.0


(*) At the same state (e_0 , σ); (**) Samples retrieved by means of freezing technique

A NON-RESONANCE METHOD MEASURING DYNAMIC SOIL PROPERTIES

Rix and Meng (2004)



DAMPING RATIO



- Small strain shear modulus G₀ little affected by tenfold change of frequency
- Small strain damping ratio D₀ more sensitive to tenfold change of frequency

LABORATORY ASSESSMENT OF G₀ EMPLOYING PIEZOELECTRIC TRANSDUCERS

ENERGY TRANSMISSION THROUGH CONTINUUM:

LABORATORY SPECIMENS = HOMOGENEOUS MEDIUM:


Tanaka et al. (1994, 1998, 2000), Anh Dan et al. (2002),

Above issues not sufficient to explain scatter observed in experimental data, Arroyo (2003)

(*) Especially relevant for gravelly geomaterials


EFFECT OF GRAIN SIZE ON LABORATORY SEISMIC TESTS RESULTS

Tanaka et al. (1994, 1998, 2000), Anh Dan et al. (2002), Maqbool et al. (2004)




(*) V_s (cyclic) from G_0 (small unload-reload loop)

VERTICAL STRAIN AND YOUNG MODULUS DECAY UNDER PIER 2P*-AKASHI KAIKYO BRIDGE




SHEAR MODULUS OF TWO GRAVELLY SOILS FROM TRIAXIAL TESTS

Adapted after Goto et al. (1994)



NORMALIZED SHEAR MODULUS OF TWO GRAVELLY SOILS FROM TRIAXIAL TESTS

Adapted after Goto et al. (1994)




G-130 BAN-31

SHEAR MODULUS OF TWO GRAVELLY SOILS FROM CYCLIC TRIAXIAL TESTS


Holocene Tokyo Gravel

Hatanaka et al. (1988)



Pleistocene Gravel, K-site


Kokusho and Tanaka (1994)



(*) Retrieved by means of freezing technique


NORMALIZED SHEAR MODULUS OF TWO GRAVELLY SOILS FROM CYCLIC TRIAXIAL TESTS

Adapted after Hatanaka et al. (1988) and Kokusho and Tanaka (1994)



NORMALIZED SHEAR MODULUS OF FUJISAWA SAND UNDISTURBED vs. RECONSTITUTED SAMPLES

Katayama et al. (1986), Ishihara (1996)




LABORATORY DETERMINED STIFFNESS DEGRADATION CURVES


Comparison of $G/G_o - log \gamma$ (undisturbed) vs. $G/G_o - log \gamma$ (reconstituted)*:

- Very similar, Goto et al. (1992, 1994), Yasuda et al. (1994), Hatanaka and Uchida (1995), Ishihara (1996)
- Degradation of $G/G_o \log \gamma$ of undisturbed soil can be more pronounced than for reconstituted* material, Ishihara (1996)
- Similar contradictory experimental results can be found as far as increase of damping ratio D with increasing $\log \gamma$ is concerned
 - (*) Reconstituted at the <u>same state</u> (e_0 , σ ') and normalized with respect to <u>field determined</u> G_0


RELATIONSHIP BETWEEN GIG₀ AND SHEAR STRAIN OBTAINED FROM CYCLIC TRIAXIAL TESTS ON GRAVEL



RELATIONSHIP BETWEEN DAMPING RATIO AND SHEAR STRAIN OBTAINED FROM CYCLIC TRIAXIAL TESTS ON GRAVEL




SOIL NON-LINEAR STIFFNESS: SIMPLE DESIGN PROCEDURE



Ticino Sand (silica)OCR α for $E_{0.1}/E_0$ α for $E_{1.0}/E_0$ 1 2.91 ± 0.33 3.72 ± 0.60 2 to 3 1.49 ± 0.21 3.41 ± 0.29 6 to 8 1.19 ± 0.21 1.95 ± 0.13

Atkinson (2000), Barbero (2001), Bovolenta (2003)




$$E_0$$
 at $\varepsilon \leq \varepsilon_t^{\ell}$
 $E_{0.1}$ at $\varepsilon = 0.1\%$ or s/B=0.1
 $E_{1.0}$ at $\varepsilon = 1\%$ or s/B=1

(*) See also Barbero (2001) and Bovolenta (2003)

SIGNIFICANCE OF STATE PARAMETER FOR COARSE GRAINED GEOMATERIALS

Jefferies and Been (1985), Hird and Hassona (1986), Konrad (1993), Leroueil and Hight (2002)



State parameter, ξ:

$$\xi_A = e_{\lambda}(A) - e_{ss} \longrightarrow \text{negative}$$

$$\xi_A = e_{\lambda}(B) - e_{ss}$$
 positive

A substitute of OCR:

$$\frac{\sigma'_{ss}}{\sigma'_{m}} = \exp(2.3 \frac{\xi}{\lambda})$$

Mean effective stress



- Phenomenological framework behaviour as proposed by Jardine (1985) and Jardine et al. (1991) can satisfactorily describe stress-strain response of gravelly geomaterials
- Among penetration tests, SPT and LPT, normalizing the results with respect to the energy delivered to the driving rods and to the effective overburden stress, appear most suitable for the soils in question

- On the increase applications of in situ geophysical methods for multipurpose geotechnical site characterization
- Of them, the most relevant are:
 - Assessment of small strain shear modulus
 - Evaluation of in situ porosity in fully saturated deposits
 - Simultaneous evaluation of small strain shear modulus and damping ratio profiles from multi station SASW method
 - Use of shear wave velocity for evaluating liquefaction susceptibility


- Initial small strain ($\varepsilon \le \varepsilon_t^\ell$) shear (G_o) and Young's (E_o) are reliably assessed from laboratory tests on <u>undisturbed</u> samples of gravelly soils when <u>local strains</u> are measured
- Stiffness of <u>undisturbed</u> gravelly geomaterials at small and intermediate strain is higher than those reconstituted, with same void ratio and subject to same consolidation stress, difference increases with increasing deposit's age
- Use of seismic tests in laboratory is subject to a number of stringent requirements as far as near-field effects and specimen homogeneity conditions are concerned


- G/G_o vs. log_γ degradation curves* as obtained from laboratory tests on undisturbed samples are representative for in situ stiffness non-linearity
- The same hypothesis applied to the G/G_o vs. log_γ curves* obtained from laboratory tests on reconstituted specimens still questionable, see Ishihara (1996)

(*) In both cases reference is made to the field determined G_o

APPROACH TO LARGE-STRAIN DYNAMIC IN SITU TEST

Stokoe et al (2001)





COSTRAINED COMPRESSION WAVES

SHEAR WAVES

UNDISTURBED SAMPLE OF GRAVELLY SOIL

By courtesy of Tokyo Soil Research Co. Ltd.



G-130

BAN-51





G-133


CAI-05

SEISMIC TESTS IN CALIBRATION CHAMBER RECONSTITUTED TICINO RIVER GRAVELLY SOILS

Brignoli et al. (1997), Ismes (1998)


Test material

Mix -	A	C	E	Ba
GC %	18.3	38.2	65.1	77.5
SC %	81.7	61.8	34.9	17.8
FC %	3.8	3.2	2.1	4.9
D_{50} mm	0.433	0.693	3.751	7.965
U_c -	6.1	17.2	32.1	25.2
e _{max} -	0.633	0.433	0.382	0.477
e _{min} -	0.362	0.258	0.177	0.246



SEISMIC TESTS IN CALIBRATION CHAMBER RECONSTITUTED TICINO RIVER GRAVELLY SOILS

Brignoli et al. (1997), Ismes (1998)



G-130

BAN-01

SEISMIC TESTS IN CALIBRATION CHAMBER RECONSTITUTED TICINO RIVER GRAVELLY SOILS EMPIRICAL EQUATIONS FITTING EXPERIMENTAL DATA

Roesler (1979), Bellotti et al. (1996), Weston (1996)

$$V_{s} = C_{s} \sqrt{F(e)} (\sigma'_{a})^{na} (\sigma'_{b})^{nb} p_{a}^{(1-na-nb)}$$

$$na + nb = 0.22 \, U_c^{0.09}$$

$$C_{\rm S} = 207 \, U_{\rm C}^{-0.08}$$

$$X = -0.54$$

$$R^2 = 0.97$$

$$s_{yx} = 21 \, m/s$$

$$V_p = C_p \sqrt{F(e)} (\sigma'_a)^{na} (\sigma'_b)^{nb} \rho_a^{(1-na-nb)}$$

$$na + nb = 0.22 U_c^{0.07}$$

$$C_p = 350 \, U_c^{-0.03}$$

$$x = -0.39$$


$$R^2 = 0.96$$

$$s_{yx} = 36 \, m/s$$

MULTIPLE YIELD SURFACES AND SOIL RESPONSE

Jardine et al (1991), Hight and Higgins (1994), Leroueil and Hight (2003)

Δu



Zone 1: $\varepsilon \leq \varepsilon_t^{\ell}$


Zone 2: $\epsilon_t^{\ell} < \epsilon \le \epsilon_t^{\nu}$

Zone 3: $\varepsilon > \varepsilon_t^{\vee}$

D

POISSON'S RATIO V', AT SMALL STRAIN AS FUNCTION OF STRESS RATIO

Hoque (1996)



SHEAR MODULUS AND DAMPING RATIO OF FUJISAWA SAND UNDISTURBED vs. RECONSTITUTED SAMPLES

Katayama et al. (1986), Ishihara (1996)

